LID 560ISO



- Smallest portable reader
- Simple operation
- Versatile multi-system reader
- Low cost, economical scanning solution



The LID-560ISO ISO Pocket Reader is a low-cost portable reader for applications that do not require maximum read range performance. Typical applications include dog breeders' individual operations and pet I.D. in veterinary practices. With its easy point-and-shoot operation, the Pocket Reader is designed for situations where no communication with an external PC or terminal is required. The reader scans a tag and displays the ID number on its LCD. A quick push of the button shows the last tag number read. The attached belt clip allows you to carry this small ergonomic unit with you on the go. The LID-560ISO ISO Pocket Reader will read TROVAN UNIQUE™ transponders, Destron FECAVA/HomeAgain transponders and their clones, as well as FDX-B transponders.

OPTIONAL ADDITIONAL EQUIPMENT BT-570 Protective rubber boot



DIMENSIONS 69.8 mm (2.7 in.) Width 125.4 mm (4.9 in.) Length Height 24 mm (0.9 in.) WEIGHT 120 gr. SUPPLY VOLAGE 9 V battery SUPPLY CURRENT Antenna activated 173 mA Antenna deactivated 26 mA BATTERY LIFE Approx. 1 hour (continuous read) DISPLAY LCD (2 lines x 16 characters) TYPICAL READING TIME 24 ms MATERIAL ABS UL 94 H **OPERATING TEMPERATURE** 0° C to +70°C (32°F to +158°F) **IDENTIFICATION CODE** 64 bits, factory pre-programmed **READING DISTANCE** ID-100 up to 50 mm (1.97 in.)ID-200 up to 75 mm (2.95 in.) up to 45 mm (1.77 in.) ID-300 ID-400 up to 130 mm (5.12 in.) up to 50 mm (1.97in.) ID-162 up to 25 mm(1 in.)Destron clones AVID encrypted up to 30 mm (1.18 in.) (13 mm length)

PRESENTED BY: