

LID 200



- Re-chargeable battery
- Single push button operation
- Small, convenient, ergonomic
- Auto sleep function

trovan[®] LID 200

The LID 200 Ring Scanner will read FDX-B (15-digit) microchips for animal identification. It has a small, convenient form factor and unique ergonomic proposition. It has an internally rechargeable battery, which may be-recharged via its mini USB comm port. The scanner comes with a CD for installing the relevant scanner drivers and software in your PC. It has single push button operation and an auto sleep function if not reactivated for within 40 seconds.

RING SCANNER

DIMENSIONS

135 x 33 mm.

WEIGHT

170 gr.

STANDARDS

ISO 11784/ISO11785 FDX-B

BATTERY

Internal lithium polymer rechargeable

Recharge via USB port

COMMS PORT

USB

AUDIO

Audible beep

DISPLAY

2 lines x 16 characters

MEMORY

last 2000 scans

ROHS COMPLIANCE

Yes

SCANS PER CHARGE

8 second scans x 1000

CHARGE TIME

3.5 hours

SOFTWARE

Windows 98 or later

OPERATING TEMPERATURE

 0° C to $+50^{\circ}$ C

TAG PROTOCOLS SUPPORTED

FDX-B 15-digit

Destron 10-digit and clones

AVID 9-digit encrypted

OPTIONS

LG-200C Car charger

LG-200W Wall plug in charger